

AUTOMATIC PET FOOD DISPENSING DEVICE

By

SUNG HO PARK

5

BACKGROUND OF THE INVENTION

The present invention relates to an improved automatic pet food dispensing device. More particularly, this invention relates to an automatic pet food dispensing device that will prevent over or underfeeding of pets and food from jamming in the feeder.

Automatic pet food dispensing devices are widely used to feed pets and animals, especially when the pet owner is away from the pet for a period of time. The diet of pets and animals is important to the their health. In order to control the diet, quantity and timeliness of feeding should be considered. Automatic pet food dispensing devices allow pets to be fed regularly and in controlled amounts.

It has been difficult for pet owners to regularly feed their pets. Misfeeding occurs in some of the situations as follows:

- 1) The pet keeper is not able to come home to feed the pet;
- 2) The pet keeper is away for an extended period of time and requires a pet sitter or a kennel, both of which may be costly to the pet owner;

1

"EXPRESS MAIL" MAILING LABEL NUMBER E0265964300 US
DATE OF DEPOSIT: 9 / 16 / 03
I HEREBY CERTIFY THAT THIS PAPER OR FEE IS BEING DEPOSITED WITH THE UNITED STATES POSTAL SERVICE "EXPRESS" MAIL POST OFFICE TO ADDRESSEE SERVICE UNDER 37 CFR 1.10 ON THE DATE INDICATED ABOVE AND IS ADDRESSED TO MAIL STOP PATENT APPLICATION, COMMISSIONER FOR PATENTS P.O. BOX 1450 ALEXANDRIA, VA 22313-1450
BY [Signature] PRINT Hana Choi

3) Multiple family members feed the pet at different times and overfeed the pet.

To remedy these situations, numerous pet food dispensers have been provided in the prior art. Examples of automatic pet feeders include U.S. Patent Nos. 4,665,862 to Pitchford, Jr.; 4,735,171 to Essex; 5,363,805 to Wing; 6,135,056 to Kuo; and 6,401,657 to Krishnamurthy. However, each of these feeders is subject to either food jams or crush especially in the in the places where the pet food enters or dispenses due to the use of augers for funneling food.

SUMMARY OF THE INVENTION

The present invention contrives to provide an automatic pet food dispensing device that solves the disadvantages of the prior art.

Accordingly, it is an object of the present invention to provide an automatic pet food dispensing device that prevents the jamming of the feeder by the food.

It is an additional object to provide such a pet food dispensing device that can control the quantity of food given to the pet per feeding.

A further object is to provide an automatic pet food dispensing device that allows for preset definite feeding times and multiple feedings in a single day.

It is a still further object to provide such an automatic pet food dispensing device that is simple to operate and safe for both the pet and the owner.

To achieve the above objectives, an automatic pet food dispensing device includes a container that stores pet food, a circular pipe attached below the container, a dispenser rotatably received in the circular pipe, a motor that rotates the dispenser, and one or more dispensing spouts connected to the circular pipe. The dispenser includes a shaft with a rectangular cross section and two or more circular dispensing discs fixed to the shaft, and each of the dispensing discs has a cut out of predetermined angle of about ninety (90) degrees.

The cut out of the dispensing discs are positioned opposite of each other. The distance between each of the dispensing discs is about one and half (1½) inches.

One end of the shaft is connected to the motor by way of a sleeve. The end of the shaft has a shape of a half circle and the sleeve has a receiving recess that receives the end of the shaft. The receiving recess has a shape of a partially flattened circle so that there is a gap between the end of the shaft and the receiving recess.

The container of the pet food dispensing device has a shape of inverted cone with an upper open end and a lower open end. The lower open end is connected to the circular pipe and the upper open end has a peripheral

edge with a cross section that has a shape of a half circle that is opened downward. This blocks intrusion of ants to the pet food.

The container, the circular pipe, the dispenser, the motor, and the dispensing spouts, are all enclosed by a case member that has an open upper top portion with a space between the peripheral edge of the container and the open upper top portion. The case member has one or more hooks where bowls can be attached to the case member with the hooks.

The container further includes an extender to increase pet food containing capacity. The extender includes a fixed annular member and a movable annular member that is received in the fixed annular member when the container is not extended, and extended upward from the fixed annular member when the container is extended.

The automatic pet food dispensing device has a power supply that supplies power to the motor, a timer, a switch and a display. The timer controls the operation time of the motor and the switch sets the timer, while the display displays parameters for setting the timer.

The dispensing discs have evenly spaced grooves cut out around the circumference of each disc. The dispensing discs also have convex bumps protruding upward therefrom.

The advantages of the present invention are an automatic pet food dispensing device that prevents food

from jamming in the feeder, easy separation of the parts
of the feeder for ease of use and ease of cleaning,
timely feeding of the pet, feeding of predetermined
quantity of pet food and prevention of ants from reaching
5 the pet food.

Although the present invention is briefly
summarized, the above objectives, as well as others, will
become apparent upon reference to the following detailed
description, accompanying drawings, and appended claims.

10

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects and advantages of
the present invention will become better understood with
reference to the accompanying drawings, wherein:

15 FIG. 1 is a front elevation view of an automatic pet food
dispensing device according to the present invention;
FIG. 2 is a cross-sectional view of the automatic pet
food dispensing device taken along line 2-2 of FIG. 1;
FIG. 3 is a perspective view of a shaft for use in
20 connection with the present invention;
FIG. 4 is an enlarged detailed cross-sectional view of
"A" of the pet food dispensing device of FIG. 1 showing
the relationship between the shaft and a sleeve;
FIG. 5 is an enlarged detailed cross-sectional view of
25 the shaft and sleeve taken along line 5-5 of FIG. 4;

FIG. 6 is a block diagram of the electrical scheme of the present invention;

FIG. 7 is an elevation view of the shaft and dispensing discs;

5 FIG. 8 is a top view of the dispensing disc;

FIG. 9 is a top view of another embodiment of the dispensing disc; and

FIG. 10 is a cross-sectional view of the dispensing disc along line 10-10 of FIG. 9.

10

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 1 and 2 show an example of an embodiment of the automatic pet food dispensing device, generally designated as 10, according to the invention.

15 The pet food dispensing device 10 comprises a container 12 for storing pet food and a case member 14. The container 12 is removably received in the case member 14. The case member 14 is elevated from the ground by legs 16. The case member 14 has dispensing spouts 28 on
20 opposite ends of each other where the pet food is dispensed. The case member 14 has hooks 18 attached on opposite ends on the side adjacent from the sides with the dispensing spouts 28 for attaching bowls 20 for drinking. The case member 14 has a power switch 22 to
25 turn the automatic pet feeder 10 on or off. Positioned adjacent to the power switch 22 are programming buttons

24 for programming the automatic pet feeder 10 to control frequency and quantity of food dispensed into feeding plates 42. A digital display 26 indicates whether the automatic pet feeder 10 is on or off as controlled by the power switch 22 and the programmed times and food quantity as controlled by the programming buttons 24.

The container 12 has the shape of an inverted cone with an open upper end 58 and a lower open end 32 connected to a hollow circular pipe 30. The container may further have an extender 90, which is provided upward from the inverted cone. The extender 90 comprises a fixed annular member 92 and a movable annular member 94 that is received in the fixed annular member 92 when the container 12 is not extended, and extended upward from the fixed annular member 92 when the container 12 is extended. The extender 90 increases the capacity of the container 12 when a large capacity is needed like when the owner of the pet is away for a few days.

The open upper end 58 has a peripheral edge 56 that has a cross-section in the shape of a downward opening half circle. A cover 90 is provided on the upper open end 58. The case member 14 encloses the container 12, the circular pipe 30, a dispenser 34, a motor 36, and the dispensing spouts 28. The peripheral edge 56 of the container 12 is not enclosed by the case member 14 and is spaced from the open upper top portion 66 of the case

member 14 to prevent ants from crawling up the case

member 14 and into the open upper end 58 of the container

12 and reaching the food inside. The circular pipe 30

rotatably receives the dispenser 34. The motor 36 rotates

5 the dispenser 34. The bottom end of the circular pipe 30

is connected to the dispensing spouts 28 where the pet

food exits into the feeding plates 42.

As shown in FIG. 3, the dispenser 34 comprises a

shaft 40 with a rectangular cross-section and two

10 dispensing discs 38 fixed to the shaft 40. The shaft 40

runs perpendicularly through the center of each

dispensing disc 38. The dispensing discs 38 each have an

arc recess 44 of a predetermined angle α as shown in FIG.

8. Preferably, the predetermined α is about ninety (90)

15 degrees. The distance L between the two dispensing discs

38 is about one and one-half (1½) inches. The arc

recesses 44 on opposite sides of one another are about

one hundred eighty (180) degrees apart. Pet food grains

are moved by gravity through the arc recesses 44 of the

20 rotating dispenser 34. When the dispenser 34 stops

rotating, dispensing of pet food also stops due to

friction of grains with the circular pipe 30 and the

dispensing discs 38 and because the circular recesses 34

are arranged opposite with respect to the shaft 40.

The shaft 40 has a bottom end 50 that has the shape of a half-circle. The bottom end 50 is fitted into a sleeve 51 that has a receiving recess 63. As shown in FIG. 4, there is a small gap between the bottom end 50 and the receiving recess 63 provided by partially flattened circle shape of the receiving recess 63 as shown well in FIG. 5. This gap induces some rattling of the dispenser 34, and stirs pet food grains. The rectangular shaft 40 also stirs pet food grains since radial distance between the shaft 40 and the circular pipe 30 changes as the shaft 40 is rotated. These stirring effects facilitates dispensing flow of pet food. Jamming is effectively prevented since pet food grains are actively stirred by the rotation of the dispenser 34 and drop through the arc recesses 44 rather than being forced to move by a feeding screw.

Referring back to FIG. 2, a driven bevel gear 60 with 48 teeth is attached parallel to the sleeve 50 via a pin 64. The pin 64 is secured by an upside down L-shape bracket 62. The driven bevel gear 60 engages with a driving bevel gear 65 having 16 teeth and connected the motor 36, thereby providing 3 to 1 speed reduction. The rotation of the motor 36 prompts the rotation of the gear 60 and all parts connected to the gear 60, including the pin 64, sleeve 50, shaft 40, dispensing discs 38 and the entire dispenser 34.

FIG. 6 shows timed operation of the automatic pet food dispensing device 10. The power switch 22 triggers either the motor 36 or the timer 54. The timer 54 is electrically connected to the motor 36 and the display 26. The display 26 shows the time that has been set for the automatic pet food dispensing device 10 to turn on. The power supply 52 supplies power to the motor 36 and the timer 54. The power supply 52 can be energized by either a battery or an AC outlet.

FIG. 7 shows another dispenser 70 that has four dispensing discs 38. The arc recesses 44 of the dispensing discs 38 are arranged so that they do not overlap with one another. The increased number of the discs 38 increases the precision of the dispensed amount.

FIGS. 9 and 10 show another embodiment of a dispensing disc 80. The dispensing disc 80 has evenly spaced grooves 46 cut out around the circumference. The grooves 46 provide additional space between the dispensing discs 80 and the circular tube 30 to allow for crumbs of the pet food to fall to the dispensing spouts 28 instead of jamming and slows down the rotation of the dispenser 34.

The dispensing disc 80 also has evenly spaced radial convex bumps 48 slightly protruding upward therefrom. As the dispensing disc 38 is rotated, the bumps 48 move

grains of pet food up and down, and thus stir the grains.

This facilitates smooth and fast dispensing of pet food.

To use the automatic pet food dispensing device 10,
place the container 12, with the open upper end 58 facing
5 upward in the open upper top portion 66 of the case
member 14, and deposit pet food in the open upper end 58.
A feeding plate 42 should be placed under the dispensing
spout 28. The operator of the automatic pet food
dispensing device 10 may either push the power switch 22
10 to turn the automatic pet food dispensing device 10 on or
push the programming buttons 24 using the display 26 to
set the timer 54. The pet will have food according in the
feeding plate 42 according to the timer or the operator's
turning the automatic pet food dispensing device 10 on.

15 Although the invention has been shown and described
in considerable detail and are pointed out in the annexed
claims, other versions are possible by converting the
aforementioned construction. Therefore, the scope of the
invention shall not be limited by the specification
20 specified above.